



HW small distributor JUMBO with screw clamp

Order number: 7230035

Type: HWV60+10ST

Simple and reliable for hollow wall mounting

suitable for: Devices up to 63A

Dimensions

Depth	98 mm
Height	900 mm
Height of HW cut-out	860 mm
Width	365 mm
Width of HW cut-out	323 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

Material

Box material	PS
Cover material	PS
Door material	Powder-coated steel

Properties

Can be lead sealed	true
Colour	White
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	-
Impact resistance	IK07
Installation type	HW
Insulation	Protection class II
Number of compartments	70
Number of rows	5
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Design current	63 A
Design voltage	400 V
Suitable for sheet thickness	10-45 mm

Certificates & standards

CE	true
Glow wire test	850 °C
REACH	false
RoHS	true
Standards	• DIN EN 60670-1 • DIN EN 60670-24 • DIN EN 61439-1 • DIN EN 61439-3 • DIN 43871
VDE	true

Accessories

Equipped with	• 1x door with frame (T+RJUMBO60+10) • 1x cavity wall latch set (HWA set) • 4x N screw terminal 3x16mm²; 14x10mm² • PE screw terminal 6x16mm²; 28x10mm²
Recommended purchase	ADS12W