

DATASHEET

+37217



DISTRIBUTION ENCL (6x16) 96md D200 SM

Dimensions WxHxD (mm)	400x875x200
EAN	5600307038147
Rows x Modules	6x16
Application	Surface Mounted (SM)
No. Frames for DIN rail	6
Locking System	2 Flat plastic handle lock
Color	White - RAL 9010
Tariff Code	85381000
Gross Weight (Kg)	13,8
Volume (m ³)	0,095
Quantity per Pack	1

Materials

Enclosure	Plastic - PSHI
Frame and door	White lacquered aluminium
Chassis	Aluminium
BUSBARS	PA support and brass busbar

Protection and Security

Insulation Class	Class II Insulation
IP Protection Degree	54
IK Protection Degree	09
GWT	650°C
Static Load	200kg/m ³
Mechanical Reinforcement	Sim
Installation Temperature	Mín: -25°C Máx: 55°C

Electrical Features

In	125A
Ue	230V/400V~
Ui	690V
Pde – 30K	85W
Frequency	50Hz

Included Accessories

Neutral Nº Busbars	5x(1x25mm ² + 9x16mm ²) 1x(12x10mm ² + 11x16mm ²)
Earth Nº Busbars	2x(1x25mm ² + 9x16mm ²) 2x(12x10mm ² + 11x16mm ²)
Blanking Plates	2x12md
Circuit Marking Labels	Yes
Fixing Kit	Sim

Standardizing Documentation

Standards	EN 62208
Directive	2014/35/UE
Regulations	RTIEBT