

## DATASHEET

+37242



### DISTRIBUTION ENCL (7x24) 168md D200 SM

Dimensions WxHxD (mm)	550x1000x200
EAN	5600307038192
Rows x Modules	7x24
Application	Surface Mounted (SM)
No. Frames for DIN rail	7
Locking System	2 Flat plastic handle lock
Color	White - RAL 9010
Tariff Code	85381000
Gross Weight (Kg)	18,65
Volume (m <sup>3</sup> )	0,143
Quantity per Pack	1

### Materials

Enclosure	Plastic - PSHI
Frame and door	White lacquered aluminium
Chassis	Aluminium
BUSBARS	PA support and brass busbar

### Protection and Security

Insulation Class	Class II Insulation
IP Protection Degree	54
IK Protection Degree	09
GWT	650°C
Static Load	200kg/m <sup>3</sup>
Mechanical Reinforcement	Sim
Installation Temperature	Mín: -25°C Máx: 55°C

### Electrical Features

In	125A
Ue	230V/400V~
Ui	690V
Pde – 30K	113W
Frequency	50Hz

### Included Accessories

Neutral Nº Busbars	6x(1x25mm <sup>2</sup> + 9x16mm <sup>2</sup> ) 2x(12x10mm <sup>2</sup> + 11x16mm <sup>2</sup> )
Earth Nº Busbars	5x(1x25mm <sup>2</sup> + 9x16mm <sup>2</sup> ) 2x(12x10mm <sup>2</sup> + 11x16mm <sup>2</sup> )
Blanking Plates	3x12md
Circuit Marking Labels	Yes
Fixing Kit	Sim

### Standardizing Documentation

Standards	EN 62208
Directive	2014/35/UE
Regulations	RTIEBT